KERN MBC20K10M



Elegantly-shaped baby scale with EC type approval and approval for medical use



Measuring system

| Adjustment options: | External calibration |
|-------------------------------|----------------------|
| Linearity: | 10 g |
| Readability [d]: | 10 g |
| Recommended adjusting weight: | 20000000M1 mg |
| Recommended adjusting weight: | 20 kg (M1) |
| Repeatability: | 10 g |
| Resolution: | 2000 |
| Stabilisation time: | 3 s |
| Tare range: | 19,990 kg |
| Warm up time: | 10 min |
| Weighing capacity [Max]: | 20 kg |
| Weighing system: | Strain gauge |
| Weighing units: | kg |
| | |

Display

Display digit height:

2,500 cm

| Technical data about verification | |
|--|---------|
| Minimum load [Min]: | 200 g |
| Periodic Verification for Italy: | 969-112 |
| Verification approval conforming to 2014/31/EU: | yes |
| Verification by KERN possible: | yes |
| Verification class: | III |
| Verification value [e]: | 10 g |
| Functions | |
| Data hold function: | yes |
| Vibration-free weighing (Animal weighing program): | yes |
| Environmental conditions | |
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -10 °C |

| Power supplyCharging time:12 hInput voltage:100 V - 240 V 50 / 60 HzMains adapter/adapter included:CH EURO UKInarrow adapter/adapter included:CH EURO UKInarrow adapter/adapter included:CH EURO UKInarrow adapter externalPower supplyOperating time:20 hOperating time (Backlight off):40 hOperating time (Backlight on):20 hRechargeable battery:Rchrg. battery optional - internServiceServiceAdjustment at the location of installation: 961-248DAkkS Certificate:963-128Verification:965-128.CategoryBalancesProduct Group:BalancesProduct Group:24 hDimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:PlasticDimensions of display device200 x 130 x 60 mm(WxDxH):200 x 280 x 72 mmDimensions of display device200 x 130 x 60 mm(WxDxH):Level indicator:Level indicator:yes | | |
|--|--|--------------------------|
| Input voltage:100 V - 240 V 50 / 60 HzMains adapter/adapter included:CH EURO UKn/a:Mains adapter externalPower supply20 hOperating time:20 hOperating time (Backlight off):40 hOperating time (Backlight on):20 hRechargeable battery:Rchrg. battery optional - internService40Adjustment at the location of installation: 961-248DAkkS Certificate:963-128Verification:965-128.CategoryBalancesBrand:KERNCategory:BalancesProduct Group:24 hDelivery:24 hDimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:Pacted serviceConstruction200 x 130 x 60 mmWxDxH):200 x 280 x 55 mmDimensions of weighing plate (WxDxH):600 x 280 x 55 mmLevel indicator:yes | Power supply | |
| Mains adapter/adapter included:CH EURO UKMains adapter/adapter included:CH EURO UKn/a:Mains adapter externalPower supply0Operating time (Backlight off):40 hOperating time (Backlight on):20 hRechargeable battery:Rchrg. battery optional - internServiceServiceAdjustment at the location of installation: 961-248DAkkS Certificate:963-128Verification:965-128.CategoryBalancesProduct Group:BalancesProduct Group:BalancesProduct Group:24 hDimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:Parcel serviceConstruction200 x 130 x 60 mmWixDxH):200 x 280 x 55 mmWixDxH):Level indicator:Uevel indicator:yes | Charging time: | 12 h |
| n/a:Mains adapter externalPower supplyOperating time:20 hOperating time (Backlight off):40 hOperating time (Backlight on):20 hRechargeable battery:Rchrg. battery optional - internServiceAdjustment at the location of installation:961-248DAkkS Certificate:963-128Verification:965-128.CategoryBalancesProduct Group:BalancesProduct Group:Baby scalePackaging & shippingDelivery:24 hDimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:Parcel serviceConstruction200 x 130 x 60 mmWixDxH):320 x 280 x 72 mmDimensions housing (WxDxH):320 x 280 x 55 mmWixDxH):Level indicator:Upinensions of weighing plate600 x 280 x 55 mmWixDxH):Level indicator:Verificator:Yes | Input voltage: | 100 V - 240 V 50 / 60 Hz |
| Power supplyOperating time:20 hOperating time (Backlight off):40 hOperating time (Backlight on):20 hRechargeable battery:Rchrg. battery optional - internServiceRchrg. battery optional - internAdjustment at the location of installation: 961-248DAkkS Certificate:963-128Verification:965-128.CategoryBalancesProduct Group:BalancesProduct Group:BalancesProduct Group:480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:Parcel serviceConstructionPackaging (WxDxH):Casing material:PlasticDimensions housing (WxDxH):320 x 280 x 72 mmDimensions of display device (WxDxH):200 x 130 x 60 mmWixDxH):Con x 280 x 55 mmDimensions of weighing plate (WxDxH):600 x 280 x 55 mmLevel indicator:yes | Mains adapter/adapter included: | CH EURO UK |
| Power supplyOperating time:20 hOperating time (Backlight off):40 hOperating time (Backlight on):20 hRechargeable battery:Rchrg. battery optional - internServiceRchrg. battery optional - internAdjustment at the location of installation: 961-248DAkkS Certificate:963-128Verification:965-128.CategoryBalancesProduct Group:BalancesProduct Group:BalancesProduct Group:480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:Parcel serviceConstructionPackaging (WxDxH):Casing material:PlasticDimensions housing (WxDxH):320 x 280 x 72 mmDimensions of display device (WxDxH):200 x 130 x 60 mmWixDxH):Con x 280 x 55 mmDimensions of weighing plate (WxDxH):600 x 280 x 55 mmLevel indicator:yes | | |
| Operating time:20 hOperating time (Backlight off):40 hOperating time (Backlight on):20 hRechargeable battery:Rchrg. battery optional - internServiceAdjustment at the location of installation:963-128DAkkS Certificate:963-128Verification:965-128.CategoryBalancesProduct Group:BalancesProduct Group:BalancesPackaging & shipping14Delivery:24 hDimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:Parcel serviceCategory10 kg x 650 x 175 mmGross weight:6 kgNet weight:320 x 280 x 72 mmDimensions housing (WxDxH):320 x 280 x 72 mmDimensions of display device (WxDxH):200 x 130 x 60 mmDimensions of weighing plate (WxDxH):600 x 280 x 55 mmLevel indicator:yes | n/a: | Mains adapter external |
| Operating time (Backlight off):40 hOperating time (Backlight on):20 hRechargeable battery:Rchrg. battery optional - internServiceAdjustment at the location of installation:963-128DAkkS Certificate:963-128Verification:965-128.Category965-128.Brand:KERNCategory:BalancesProduct Group:Baby scalePackaging & shipping24 hDimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:PlasticDimensions housing (WxDxH):320 x 280 x 72 mmDimensions of display device (WxDxH):200 x 130 x 60 mmUirwnsking plate (WxDxH):600 x 280 x 55 mmUirwnsking plate (WxDxH):600 x 280 x 55 mmUirwnsking plate (WxDxH):Level indicator:Uirwnsking plate (WxDxH):600 x 280 x 55 mm | Power supply | |
| Operating time (Backlight on):20 hRechargeable battery:Rchrg. battery optional - internServiceAdjustment at the location of installation: 961-248DAkkS Certificate:963-128Verification:965-128.Category963-128Brand:KERNCategory:BalancesProduct Group:Baby scalePackaging & shipping24 hDimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:Parcel serviceConstruction320 x 280 x 72 mmDimensions housing (WxDxH):320 x 280 x 55 mmWxDxH):00 x 130 x 60 mmUwxDxH):200 x 130 x 60 mmWxDxH):200 x 130 x 55 mmWxDxH):Level indicator:Use Indicator:yes | Operating time: | 20 h |
| Rechargeable battery:Rchrg. battery optional - internServiceAdjustment at the location of installation: 961-248DAkkS Certificate:963-128Verification:965-128.CategoryBrand:KERNCategory:BalancesProduct Group:Baby scalePackaging & shippingDelivery:24 hDimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:Parcel serviceConstruction200 x 130 x 60 mmDimensions of display device (WxDxH):200 x 130 x 60 mmDimensions of weighing plate (WxDxH):600 x 280 x 55 mmLevel indicator:yes | Operating time (Backlight off): | 40 h |
| intern Service Adjustment at the location of installation: 961-248 DAkkS Certificate: 963-128 Verification: 965-128. Category Brand: KERN Category: Balances Product Group: Baby scale Packaging & shipping Delivery: 24 h Dimensions packaging (WxDxH): 480 x 650 x 175 mm Gross weight: 6 kg Net weight: 4,500 kg Shipping method: Parcel service Construction Casing material: Plastic Dimensions of display device 200 x 130 x 60 mm (WxDxH): 320 x 280 x 55 mm (WxDxH): binensions of weighing plate (WxDxH): binensions of weighing plate (WxDxH): yes | Operating time (Backlight on): | 20 h |
| Adjustment at the location of installation: 961-248DAkkS Certificate:963-128Verification:965-128.Category965-128.Brand:KERNCategory:BalancesProduct Group:Baby scalePackaging & shipping24 hDimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:965-128.Construction24 hCategory:24 hDimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:965-128.Dimensions packaging (WxDxH):90 kgShipping method:90 x 130 kgDimensions folisplay device200 x 130 x 60 mm(WxDxH):200 x 130 x 60 mmDimensions of weighing plate600 x 280 x 55 mm(WxDxH):yes | Rechargeable battery: | |
| DAkkS Certificate:963-128Verification:965-128.Category965-128.Brand:KERNCategory:BalancesProduct Group:Baby scalePackaging & shipping24 hDimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:Parcel serviceConstruction200 x 130 x 60 mmDimensions of display device200 x 130 x 60 mmWxDxH):Dimensions of weighing plateMxDxH):600 x 280 x 55 mmLevel indicator:yes | Service | |
| Verification:965-128.CategoryKERNBrand:KERNCategory:BalancesProduct Group:Baby scalePackaging & shippingDelivery:24 hDimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:Parcel serviceConstructionImage: Second | Adjustment at the location of installation | :961-248 |
| CategoryBrand:KERNCategory:BalancesProduct Group:Baby scalePackaging & shippingEaby scaleDelivery:24 hDimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:Parcel serviceConstructionS20 x 280 x 72 mmDimensions housing (WxDxH):320 x 280 x 72 mmDimensions of display device200 x 130 x 60 mm(WxDxH):Dimensions of weighing plate(WxDxH):600 x 280 x 55 mmLevel indicator:yes | DAkkS Certificate: | 963-128 |
| Brand:KERNCategory:BalancesProduct Group:Baby scalePackaging & shippingEaby scaleDelivery:24 hDimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:Parcel serviceConstructionSlow x 280 x 72 mmDimensions of display device200 x 130 x 60 mm(WxDxH):200 x 280 x 55 mmLevel indicator:yes | Verification: | 965-128. |
| Category:BalancesProduct Group:Baby scalePackaging & shippingEaby scaleDelivery:24 hDimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:Parcel serviceConstructionCasing material:PlasticDimensions of display device200 x 130 x 60 mm(WxDxH):200 x 130 x 55 mmDimensions of weighing plate600 x 280 x 55 mm(WxDxH):yes | Category | |
| Product Group:Baby scalePackaging & shipping24 hDelivery:24 hDimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:Parcel serviceConstructionCasing material:PlasticDimensions of display device200 x 130 x 60 mm(WxDxH):200 x 280 x 55 mmDimensions of weighing plate (WxDxH):600 x 280 x 55 mmLevel indicator:yes | Brand: | KERN |
| Packaging & shippingDelivery:24 hDimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:Parcel serviceConstructionCasing material:PlasticDimensions housing (WxDxH):320 x 280 x 72 mmDimensions of display device200 x 130 x 60 mm(WxDxH):Dimensions of weighing plateLevel indicator:yes | Category: | Balances |
| Delivery:24 hDimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:Parcel serviceConstructionCasing material:PlasticDimensions housing (WxDxH):320 x 280 x 72 mmDimensions of display device (WxDxH):200 x 130 x 60 mmDimensions of weighing plate (WxDxH):600 x 280 x 55 mmLevel indicator:yes | Product Group: | Baby scale |
| Dimensions packaging (WxDxH):480 x 650 x 175 mmGross weight:6 kgNet weight:4,500 kgShipping method:Parcel serviceConstructionPlasticCasing material:PlasticDimensions housing (WxDxH):320 x 280 x 72 mmDimensions of display device200 x 130 x 60 mm(WxDxH):Dimensions of weighing plateConstruction:yes | Packaging & shipping | |
| Gross weight:6 kgNet weight:4,500 kgShipping method:Parcel serviceConstructionPlasticCasing material:PlasticDimensions housing (WxDxH):320 x 280 x 72 mmDimensions of display device (WxDxH):200 x 130 x 60 mmDimensions of weighing plate (WxDxH):600 x 280 x 55 mmLevel indicator:yes | Delivery: | 24 h |
| Net weight:4,500 kgShipping method:Parcel serviceConstructionPlasticCasing material:PlasticDimensions housing (WxDxH):320 x 280 x 72 mmDimensions of display device200 x 130 x 60 mm(WxDxH):Dimensions of weighing plateDimensions of weighing plate600 x 280 x 55 mm(WxDxH):yes | Dimensions packaging (WxDxH): | 480 x 650 x 175 mm |
| Shipping method:Parcel serviceConstructionPlasticCasing material:PlasticDimensions housing (WxDxH):320 x 280 x 72 mmDimensions of display device200 x 130 x 60 mm(WxDxH):Dimensions of weighing plateDimensions of weighing plate600 x 280 x 55 mm(WxDxH):yes | Gross weight: | 6 kg |
| ConstructionCasing material:PlasticDimensions housing (WxDxH):320 x 280 x 72 mmDimensions of display device200 x 130 x 60 mm(WxDxH):000 x 280 x 55 mmDimensions of weighing plate600 x 280 x 55 mm(WxDxH):200 x 100 x 280 x 55 mmLevel indicator:yes | Net weight: | 4,500 kg |
| Casing material:PlasticDimensions housing (WxDxH):320 x 280 x 72 mmDimensions of display device (WxDxH):200 x 130 x 60 mmDimensions of weighing plate (WxDxH):600 x 280 x 55 mmLevel indicator:yes | Shipping method: | Parcel service |
| Dimensions housing (WxDxH):320 x 280 x 72 mmDimensions of display device (WxDxH):200 x 130 x 60 mmDimensions of weighing plate (WxDxH):600 x 280 x 55 mmLevel indicator:yes | Construction | |
| Dimensions of display device (WxDxH):200 x 130 x 60 mmDimensions of weighing plate (WxDxH):600 x 280 x 55 mmLevel indicator:yes | Casing material: | Plastic |
| (WxDxH): 600 x 280 x 55 mm Dimensions of weighing plate 600 x 280 x 55 mm (WxDxH): ves | Dimensions housing (WxDxH): | 320 x 280 x 72 mm |
| (WxDxH): Level indicator: yes | | 200 x 130 x 60 mm |
| Level indicator: yes | Dimensions of weighing plate | 600 x 280 x 55 mm |
| - | , | yes |
| | Material weighing plate: | Plastic |
| Overall dimensions mounted 600 x 407 x 120 mm | • • • | 600 x 407 x 120 mm |
| (WxDxH): | (WxDxH): | |
| Revolving screw feet: yes | Revolving screw feet: | yes |
| Weighing surface (WxD): 600 x 280 mm | Weighing surface (WxD): | 600 x 280 mm |

KERN MBC20K10M



Elegantly-shaped baby scale with EC type approval and approval for medical use

Piktogramme

STANDARD



OPTION



FACTORY

