

MASTERLIGHT® LED

UNTERSUCHUNGSLEUCHE | EXAMINATION LAMP

MASTERLIGHT® LED, 5-Fuß-Stativ, 7W | MASTERLIGHT® LED, 5-foot stand, 7W

REF 10.11020.002

LED	LED-Lampe 7 Watt
50.000 h	Lebensdauer der LED-Lampe
7.500 Lux	Beleuchtungsstärke (bei 0,4 m Arbeitsabstand)
EU / GB / US	mit wechselbarem Netzstecker

LED bulb: 7 Watts
Lifespan of the LED light
Illumination intensity (at a working distance of 0.4 m)
With universal power plug



Flexible LED-Leuchte mit 5-Fuß-Fahrstativ aus hochwertigem Edelstahl

- modernes, schlankes Design
- punktgenaues Licht – angenehm und wunschgemäß verstellbar
- Netzspannung 100 - 240V, 50 - 60 Hz
- LED-Lampe
- Abstrahlungswinkel 24°
- Farbtemperatur ca. 2700° Kelvin
- einfache und schnelle Montage
- mit wechselbarem Netzstecker
- Rollen: 2x mit Bremse, 1x antistatisch und 2x normal

Flexible LED examination light with 5-foot, rolling floor stand made of high-quality stainless steel

- modern, slim design
- precise light spot – easy to use, infinitely adjustable
- supply voltage 100 - 240V, 50 - 60 Hz
- LED bulb
- reflection angle: 24°
- colour temperature: approx. 2700° Kelvin
- easy and quick assembly
- with universal power plug
- casters: 2x with brake, 1x anti-static and 2x normal

Technische Daten

Technical data

Leuchtfeldgröße (bei 0,5 m Arbeitsabstand)	Light spot size (at a working distance of 0.5 m)	100 mm
Arbeitsbereich (bei 0,5 m Arbeitsabstand)	Working area (at a working distance of 0.5 m)	125 mm
Maximale Höhe	Maximum height	211 cm
Maximaler Arbeitsbereich	Maximum working area	170 cm
Gewicht (netto)	Weight (net)	4,7 kg
Stativrohr, Edelstahl	Stand post, stainless steel	97,5 cm
Fußrohr, Edelstahl	Feet, stainless steel	30 cm

ERSATZTEILE | SPARE PARTS

LED-Ersatzlampe | Spare LED bulb

für MASTERLIGHT® LED,
LED-Reflektorlampe
Abstrahlungswinkel 24°

for MASTERLIGHT® LED,
LED reflector bulb
angle of reflection: 24°



LED | LED 7W

REF 10.90120.002