

HEINE Headlights



Technical Data			
Type of Light	LED	LED	F.O.
Light Intensity (at 250 mm working distance)	<b>Up to 40,000 Lux</b>	<b>Up to 50,000 Lux</b>	<b>Up to 35,000 Lux</b> with HK 7000 Projector
Colour Temperature (Kelvin)	<b>4,500 K</b>	<b>4,500 K</b>	<b>3,300 K</b> with HK 7000 Projector
Spot Size (at 420 mm working distance)	<b>81 mm</b>	<b>30 – 80 mm</b>	<b>40 – 150 mm</b>
Power Sources/ operating time	mPack LL <b>17 hours</b>	mPack UNPLUGGED <b>3.5 hours</b> mPack <b>8.5 hours</b>	F.O. Projector
Weight	<b>50 g</b> with S-FRAME <b>165 g</b> with Lightweight Headband	<b>260 g</b> <b>460 g</b> with mPack UNPLUGGED	<b>435 g</b>
Angle of Declination	Fully-adjustable	Fully-adjustable	Fully-adjustable
Light Intensity Control	<b>0 – 100 %</b>	<b>0 – 100 %</b>	<b>0 – 100 %</b>
Features			
Adjustable Spot Size	--	<input type="checkbox"/>	<input type="checkbox"/>
Waterproof	<input type="checkbox"/>	--	--
Optional Yellow Filter	<input type="checkbox"/>	<input type="checkbox"/>	--
Polarisation Filter	--	<input type="checkbox"/>	--
Expandable with HR and HRP Loupes	--	<input type="checkbox"/>	<input type="checkbox"/>
Optional Video Version	--	<input type="checkbox"/>	--
Head-worn	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Spectacle-worn	<input type="checkbox"/>	--	--
Page	116 – 117	118 – 122	123



## HEINE® LED MicroLight

### Ultralight Universal Headlight – now with LED<sup>HQ</sup>



**LED<sup>HQ</sup>**  
LED NOW IN HEINE QUALITY.

∴ Compact and Lightweight

∴ Coaxial Illumination


∴ Up to 40,000 Lux/250mm distance




- ∴ **LED in HQ** – the new standard in LED illumination defining optimal light intensity, homogeneity and colour rendering for each individual examination situation.
- ∴ **Compact and lightweight.** Ensures perfect comfort.
- ∴ **Aluminium Housing.** Exclusive aluminum housing protects the optics against dust and moisture to ensure an extraordinary long lifespan.
- ∴ **Coaxial Illumination:** Compact coaxial design ensures a completely shadow-free image and allows for excellent illumination of difficult to see areas.
- ∴ **Homogeneity:** An absolutely bright light spot that is uniform from edge-to-edge for the perfect illumination in all examination situations.

#### Technical Specification

Illumination	Up to <b>40,000 Lux</b> at a working distance of 250mm
Colour Temperature	<b>4,500 Kelvin</b>
LED Operating Life	Up to <b>50,000 hours</b>
Weight	50g together with S-FRAME, 165g together with Lightweight Headband
Angle of Declination	Stepless and individually adjustable for every examination
Operating Time	<b>17 hours</b> of continuous ON time at full power with mPack LL



Conventional System [01]



HEINE Precision Lens System [02]

- ∴ **Precision multiple lens optical system** consisting of four high-quality lenses. Completely homogeneous illumination of the whole field of view, and a clearly defined light spot.

#### Mounting Options:



#### ∴ HEINE S-FRAME®

- ∴ **Maximum comfort** with a modern, ergonomic design.
- ∴ **Malleable temples and nose pad.** Can be customized to fit any face perfectly.
- ∴ **Innovative materials** – Carbon-Kinetium reduces weight (50g together with LED MicroLight).
- ∴ **Tough polycarbonate protective lenses.**



#### ∴ HEINE® Lightweight Headband

- ∴ **Lightweight** (165g together with LED MicroLight.) Ideal for spectacle wearers.
- ∴ **Fully-adjustable for width to fit any head.**
- ∴ **Hygienic and comfortable leather cushions.**

## HEINE® mPack LL

### Power Source



- ∴ **Portable power pack.** Does not tie the user to desk, wall or static power supplies.
- ∴ **Li-ion Technology.** Triple capacity compared with current NiCd systems.  
No memory effect, autonomy for 17 hours of continuous ON time at full power.
- ∴ **Fast Charge.** Charges to full capacity in 2 hours.
- ∴ **Charge Status Display.** Always lets you know how much operating charge you have left.
- ∴ **Stepless light intensity control.** Optimum brightness setting prevents reflexes.
- ∴ **Flexible Charging Options:** EN50 Desk and wall charger, or plug-in transformer.
- ∴ **Intelligent.** Can be used as mains power supply even while in “charge” mode.
- ∴ **100 – 240V Compatible Transformer** incl. 4 plugs for world wide compatibility.

For the optional EN50 table/wall unit please see page 133.

## HEINE® LED MicroLight

### Ordering Information



[01]

[02]



[03]

#### LED MicroLight

on S-FRAME with mPack LL, plug-in transformer, retaining cord and cleaning fluid in case [01]	<b>J-008.31.270</b>
on Lightweight Headband with mPack LL and plug-in transformer in case [02]	<b>J-008.31.275</b>
Detachable Yellow Filter [03]	<b>C-000.32.241</b>



## HEINE® ML 4 LED HeadLight

### Ultra bright coaxial illumination – Now with LED<sup>HQ</sup>



LED<sup>HQ</sup>

LED NOW IN HEINE QUALITY.

Comfortable and secure fit

Adjustable spot size

Flexible Power Source Options

- ⌘ **LED in HQ** – the new standard in LED illumination defining optimal light intensity, homogeneity and colour rendering for each individual examination situation.
- ⌘ **Adjustable illumination spot size:** 30 mm to 80 mm spot size range (at 420 mm working distance) to fit any examination situation.
- ⌘ **Bright and Homogenous Illumination.** Absolutely bright light spot that is uniform from edge-to-edge for the perfect illumination in all examination situations.
- ⌘ **Stepless light intensity control.** Optimal brightness setting prevents reflexes.
- ⌘ **Flexibility.** Flexible Power Source Options: 100 % mobility with a choice of cable-free mPack UNPLUGGED head-worn battery or mPack belt-worn battery pack.
- ⌘ **Coaxial Illumination.** Coaxial design ensures a completely shadow-free image and allows for excellent illumination of difficult to see areas.
- ⌘ **Comfortable and secure fit.** The ML 4 Professional headband has multiple adjustment points and soft padding for comfort and stability – even during long examinations.
- ⌘ **Optional Filters.** Polarisation filter P2 improves contrast and yellow filter reduces blue light.

#### Technical Specification

Illumination	Up to <b>50,000 Lux</b> at a working distance of 250 mm
Colour Temperature	<b>4,500 Kelvin</b>
LED Operating Life	Up to <b>50,000 hours</b>
Spot Adjustment	<b>30 mm to 80 mm</b> at <b>420 mm</b> working distance
Angle of Declination	Stepless and individually adjustable for every examination
Rheostat	Headband-mounted
Operating Time	<b>8.5 hours</b> with mPack and <b>3.5 hours</b> with mPack UNPLUGGED of continuous ON time at full power

#### Power Options:

##### ⌘ HEINE® mPack

- ⌘ **Portable power pack.** Does not tie the user to desk, wall or static power supplies.
- ⌘ **Li-ion Technology. Triple capacity** compared with current NiCd systems. No memory effect, autonomy for 8.5 hours of continuous ON time at full power.
- ⌘ **Fast Charge.** Charges to full capacity in 2 hours.
- ⌘ **Charge Status Display.** Always lets you know how much operating charge you have left.
- ⌘ **Stepless light intensity control.** Optimum brightness setting prevents reflexes.
- ⌘ **Flexible Charging Options:** EN50 Desk and wall charger, or plug-in transformer.
- ⌘ **Intelligent.** Can be used as mains power supply even while in “charge” mode.
- ⌘ **100 – 240V Compatible Transformer** incl. 4 plugs for world wide compatibility.

For the optional EN50 table/wall unit please see page 133.

##### ⌘ HEINE® mPack UNPLUGGED. Headband-mounted rechargeable battery.

- ⌘ **Wireless.** 100 % mobility for absolute freedom of movement.
- ⌘ **Rechargeable battery integrated on the headband.** No inconvenient cable connections.
- ⌘ **Lightweight with balanced weight distribution.** High level of comfort.
- ⌘ **Charge Status Display** indicates remaining operating time.
- ⌘ **Intelligent.** Can be used as mains power supply even in “charge” mode.
- ⌘ **Fast Charge.** Charges to full capacity in only 2 hours. Operating time 3.5 hours of continuous ON time at full power.
- ⌘ **Top Safety Standards.** Integrated charge and performance checks during operation. Lithium polymer technology. UL compliant.



HEINE® ML4 LED HeadLight

Ordering Information



LED NOW IN HEINE QUALITY.



[01]



[02]



[03]



[04]



[05]



[06]



[07]



[08]



[09]

**ML4 LED HeadLight with Headband Professional L and Power Sources**

ML4 LED HeadLight without power source [01]	J-008.31.410
ML4 LED HeadLight with plug-in transformer [01] + [02]	J-008.31.411
ML4 LED HeadLight with mPack and plug-in transformer [01] + [03]	J-008.31.413
ML4 LED HeadLight with mPack UNPLUGGED and plug-in transformer UNPLUGGED [01] + [04]	J-008.31.415
ML4 LED HeadLight with wall mounted EN50 UNPLUGGED charger and 2x mPack UNPLUGGED [01] + [05]	J-008.31.416

**ML4 LED HeadLight accessories**

Detachable Yellow Filter [06]	J-000.31.321
Extension Cord from plug-in transformer UNPLUGGED to mPack UNPLUGGED, 2 m [07]	X-000.99.668
<b>NEW:</b> Polarisation filter P2 for ML4 LED and HR Loupes [08] + [09]	J-000.31.326
<b>NEW:</b> Spare polarisation filter P2 for HR Loupes (2 pairs) [09]	C-000.32.536



## HEINE® ML4 LED HeadLight with HR/HRP Optics



LED NOW IN HEINE QUALITY.

The ML4 LED HeadLight is optionally supplied with HR/HRP Binocular Loupes incl. i-View loupe mount and with or without S-GUARD. The binocular loupe is fully adjustable for every examiner and for every examination axis.

- **HEINE S-GUARD:** Rapid and simple symmetric adjustment of binocular loupes with splash protection by protective lenses.
- **HEINE i-View for ML4 LED HeadLight:** Provides any angle of view and flips up the optics independently of the illumination beam.



[01]



[02]

### ML4 LED HeadLight Kits with S-GUARD and Power Source

The following Kits contain: ML4 LED HeadLight, HR/HRP optics with i-View and S-GUARD, mPack and plug-in transformer [01], Cleaning Fluid [02]

Kit 1:	with <b>HR</b> Binocular Loupe	2.5x/340mm	<b>J-008.31.440</b>
Kit 2:	with HR Binocular Loupe	2.5x/420mm	<b>J-008.31.441</b>
Kit 11:	with HR Binocular Loupe	2.5x/520mm	<b>J-008.31.450</b>
Kit 3:	with <b>HRP</b> Binocular Loupe	3.5x/420mm	<b>J-008.31.442</b>
Kit 4:	with HRP Binocular Loupe	4x/340mm	<b>J-008.31.443</b>
Kit 5:	with HRP Binocular Loupe	6x/340mm	<b>J-008.31.444</b>



[01]

### ML4 LED HeadLight Kits with Power Source without S-GUARD

The following Kits contain: ML4 LED HeadLight, HR/HRP optics with i-View, mPack and plug-in transformer [01]

Kit 1c:	with <b>HR</b> Binocular Loupe	2.5x/340mm	<b>J-008.31.452</b>
Kit 2c:	with HR Binocular Loupe	2.5x/420mm	<b>J-008.31.453</b>
Kit 11c:	with HR Binocular Loupe	2.5x/520mm	<b>J-008.31.463</b>
Kit 3c:	with <b>HRP</b> Binocular Loupe	3.5x/420mm	<b>J-008.31.454</b>
Kit 4c:	with HRP Binocular Loupe	4x/340mm	<b>J-008.31.456</b>
Kit 5c:	with HRP Binocular Loupe	6x/340mm	<b>J-008.31.457</b>



[03]



[02]

### ML4 LED HeadLight UNPLUGGED Kits with S-GUARD and Power Source

The following Kits contain: ML4 LED HeadLight, HR/HRP optics with i-View and S-GUARD, Wall transformer EN50 UNPLUGGED [03], 2x mPack UNPLUGGED, Cleaning Fluid [02]

Kit 6:	with <b>HR</b> Binocular Loupe	2.5x/340mm	<b>J-008.31.445</b>
Kit 7:	with HR Binocular Loupe	2.5x/420mm	<b>J-008.31.446</b>
Kit 12:	with HR Binocular Loupe	2.5x/520mm	<b>J-008.31.451</b>
Kit 8:	with <b>HRP</b> Binocular Loupe	3.5x/420mm	<b>J-008.31.447</b>
Kit 9:	with HRP Binocular Loupe	4x/340mm	<b>J-008.31.448</b>
Kit 10:	with HRP Binocular Loupe	6x/340mm	<b>J-008.31.449</b>



[03]

### ML4 LED HeadLight UNPLUGGED Kits with Power Source without S-GUARD

The following Kits contain: ML4 LED HeadLight, HR/HRP optics with i-View, Wall transformer EN50 UNPLUGGED [03], 2x mPack UNPLUGGED

Kit 6c:	with <b>HR</b> Binocular Loupe	2.5x/340mm	<b>J-008.31.458</b>
Kit 7c:	with HR Binocular Loupe	2.5x/420mm	<b>J-008.31.459</b>
Kit 12c:	with HR Binocular Loupe	2.5x/520mm	<b>J-008.31.464</b>
Kit 8c:	with <b>HRP</b> Binocular Loupe	3.5x/420mm	<b>J-008.31.460</b>
Kit 9c:	with HRP Binocular Loupe	4x/340mm	<b>J-008.31.461</b>
Kit 10c:	with HRP Binocular Loupe	6x/340mm	<b>J-008.31.462</b>



HR/HRP Binocular Loupes – Retrofitting Sets  
for HEINE ML4 LED HeadLight



Pos. 1



[01]



Pos. 2



[02]

**Retrofitting Set HR/HRP Binocular Loupes for ML4 LED HeadLight**

The sets enable you to equip your existing ML4 LED HeadLight with a binocular loupe. The set contains HR/HRP optics with i-View, S-GUARD splash protection and cleaning fluid [01]

with <b>HR</b> Binocular Loupe	2.5x/340mm	<b>J-000.31.370</b>
with HR Binocular Loupe	2.5x/420mm	<b>J-000.31.371</b>
with <b>HRP</b> Binocular Loupe	3.5x/420mm	<b>J-000.31.372</b>
with HRP Binocular Loupe	4x/340mm	<b>J-000.31.373</b>
with HRP Binocular Loupe	6x/340mm	<b>J-000.31.374</b>

5 Steri-levers for i-View loupe mount for ML4 LED HeadLight [02]	<b>C-000.32.399</b>
--	---------------------

Power Sources



[01]



[02]



[03]


mPack and plug-in Transformer [01]	<b>X-007.99.672</b>
Plug-in Transformer for ML4 LED HeadLight [02]	<b>X-095.16.330</b>

mPack with EN50 table/wall unit (incl. 90° Angled Adaptor, Instrument support for Professional L Headband) [03]	<b>X-095.17.302</b>
---	---------------------




## HEINE® ML4 LED HeadLight with DV1 Digital Video Camera

### DV1 – for high-resolution, digital images



[01]

- ∴ **High-resolution video camera.** 1.3 Megapixel, 1,280x960 Pixel.
- ∴ **Fully-integrated camera system.** No external brackets or prisms.
- ∴ **Precise HEINE Optics.** For the best digital images and high light intensity.
- ∴ **Dustproof.** No maintenance required.
- ∴ **Focus adjustable for any working distance.** From 250 to 800mm.
- ∴ **Automatic white balance.**
- ∴ Connection of the camera via a standard USB 2.0 interface. Reliable, uncomplicated data transfer.
- ∴ **Compact.** Lightweight design (50g, camera head without cable, total weight 410g).
- ∴ **Connecting cable 3m.**
- ∴ **Perfect Integration.** HeadLight, Digital Video Camera and Optional Binocular Loupe are designed and manufactured in-house.



[02]

#### ML4 LED HeadLight with DV1

ML4 LED HeadLight with DV1 digital video camera and mPack UNPLUGGED with plug-in transformer [01]

J-008.31.470

ML4 LED HeadLight with DV1 digital video camera and mPack with plug-in transformer [02]

J-008.31.471



## HEINE® MD 1000 Fiber Optic (F.O.) Headlight



- ⌘ **Compact, high-tech optics** for homogeneous, coaxial, exceptionally-bright illumination.
- ⌘ **Ultra-light, highly-flexible fiber optic cable** with gown clips, length 3m.
- ⌘ **Height and angle of illumination adjustable by a single control.**
- ⌘ **Lightweight, flexible Headband Professional L:** Adjustable for height and width with detachable soft leather forehead cushion.
- ⌘ **Adjustable light spot** with sterilizable lever.
- ⌘ **Can be combined with HEINE HR and HRP Binocular Loupes** for magnification from 2.5x – 6x.
- ⌘ **Can be fitted with a CCD camera.**
- ⌘ **Light source: HK 7000 F.O. Projector.**

### Technical Specification

Illumination	Up to <b>35,000 Lux</b> with HK 7000 F.O. Projector at a working distance of 250 mm
Colour Temperature	<b>3,300 Kelvin</b> with HK 7000 F.O. Projector
Light Source	HK 7000 F.O. Projector
Spot Adjustment	Adjustable spot size from <b>20 mm to 70 mm</b> at a distance of 200mm and <b>45 mm to 180 mm</b> at a distance of 500 mm
Angle of Declination	Individually-adjustable
Brightness control	Stepless brightness control on Light Source

### MD 1000 F.O. Headlight

with Headband Professional L	<b>J-003.31.231</b>
------------------------------	---------------------

## HEINE® MD 1000 F.O. Headlight with HR/HRP Optics

The MD 1000 is optionally supplied with HR/HRP Binocular Loupes including i-View loupe mount and S-GUARD. The binocular loupe is fully-adjustable for every examiner and for every examination axis.

- ⌘ **HEINE S-GUARD:** Rapid and simple symmetric adjustment of binocular loupes with splash protection by protective lenses.
- ⌘ **HEINE i-View:** Provides any angle of view and flips up the optics independently of the illumination beam.



### MD 1000 F.O. Headlight with HR/HRP Binocular Loupes

The following order numbers include: MD 1000 F.O. Headlight, HR/HRP optics with i-View and S-GUARD, Cleaning Fluid

Kit 1: with <b>HR</b> Binocular Loupe 2.5x/340mm	<b>J-003.31.245</b>
Kit 2: with HR Binocular Loupe 2.5x/420mm	<b>J-003.31.246</b>
Kit 3: with <b>HRP</b> Binocular Loupe 3.5x/420mm	<b>J-003.31.247</b>
Kit 4: with HRP Binocular Loupe 4x/340mm	<b>J-003.31.248</b>
Kit 5: with HRP Binocular Loupe 6x/340mm	<b>J-003.31.249</b>

5 Steri-levers for i-View loupe mount	<b>C-000.32.399</b>
---------------------------------------	---------------------